



FABBRICA CAVI - ANTENNE - ACCESSORI TV



RG 214 U-ZH

DOUBLE SCREENED 50 OHM RF COAXIAL CABLE
MANUFACTURED IN COMPLIANCE WITH MIL-C-17F STANDARDS
COMPLIANCE IEC 60754-1 IEC 60754-2 IEC 61034-2

Class CPR **E_{ca}**

CA PE CA CA Pet LSZH
7 x 0,75 mm ø 7,25 mm ø 7,90 mm ø 8,60 mm h. 27 mm ø 10,8 mm



A B C D E F

MECHANICAL DATA

A	INNER CONDUCTOR	SILVERED COPPER	7 x 0,75 mm
B	DIELECTRIC	LOW DENSITY POLYETHYLENE	ø 7,25 ± 0,18 mm
C	1° BRAID	SILVERED COPPER	144 x 0,16 mm
	- COVERAGE		96%
D	2° BRAID	SILVERED COPPER	168 x 0,16 mm
	- COVERAGE		98%
E	NON-MIGRATING	POLYESTER TAPE	h. 27 mm
F	SHEATH	FLAME RETARDANT NON-CORROSIVE THERMOPLASTIC FREE OF HALOGENS		ø 10,8 ± 0,18 mm
	- COLOUR	BLACK - RAL 9004		
	- PRINTING	M17/75-RG214 MIL-C-17G RG 214 U-ZH 50 Ohm LSZH		
		MADE IN ITALY CE 56 WEEK/YEAR EN 50575:2014 + A1:2016 Eca		

MINIMUM BENDING RADIUS (mm)

- SINGLE ø EXTERNAL X 5
- REPEATED ø EXTERNAL X 10

TEMPERATURE RANGE -30 °C / +70 °C

CABLE WEIGHT (Kg/Km)

- COPPER 119,7
- PLASTIC 89,4
- TOTAL 209,6

ELECTRICAL PROPERTIES at 20°C

IMPEDANCE 50 ± 2 Ohm

CAPACITANCE 100 pF/m

VELOCITY RATIO 66%

RESISTANCE

- INNER CONDUCT. 6 Ohm/Km
- BRAID 4,2 Ohm/Km

TENSION

- SHEATH SPARK TESTING 5,5 kV

ATTENUATIONS dB/100 m.

		dB	W
5	MHz	1,3	
10	MHz	1,9	
50	MHz	4,5	
100	MHz	6,7	
200	MHz	9,9	
400	MHz	14,3	

MAX. POWER RATING W

		dB	W
500	MHz	16,1	
600	MHz	17,8	
800	MHz	21,3	
1000	MHz	24,3	
1350	MHz	29,7	
1500	MHz	31,7	

		dB	W
1750	MHz	35,2	
2150	MHz	40,5	
2250	MHz	41,5	
2500	MHz	44,7	
2750	MHz	47,9	
3000	MHz	51,3	

STRUCTURAL RETURN LOSS dB

30 ÷ 300 MHz	>28	1000 ÷ 2000 MHz	>22
300 ÷ 600 MHz	>26	2000 ÷ 3000 MHz	>20
600 ÷ 1000 MHz	>25 ÷	MHz -

SCREENING EFFECTIVENESS dB

100 ÷ 900 MHz	>78
900 ÷ 2000 MHz	-
2000 ÷ 3000 MHz	-

The producer reserves himself to make modification on the item without any notice.